



Cropac Equipment Inc.
800.427.6722
sales@cropac.com



2015 TADANO GR1000XL-2

TADANO

SERIAL #: 549244

Five section full power partially synchronized boom 39.4'~154.2'
33.1' or 58.1' bi-fold lattice jib
Variable speed main hoist with grooved drum
Mitsubishi 6M60-TLA3B turbo charged after cooled engine (267HP) with exhaust brake
Electronic controlled automatic transmission driven by torque converter

CALL FOR PRICE

530
HOURS

100 TN
CAPACITY

USED
CONDITION

SPECIFICATIONS

- Five section full power partially synchronized boom 39.4'~154.2' (12.0m~47.0m)
- 33.1' or 58.1' (10.1m or 17.7m) bi-fold lattice jib (tilt type) with 3.5°, 25° or 45° pinned offsets and self storing pins
- Auxiliary lifting sheave (single top) stowable
- Variable speed main hoist with grooved drum, cable follower and 797' of ¾" cable
- Variable speed auxiliary hoist with grooved drum, cable follower and 436' of ¾" cable
- Drum rotation indicator (thumper type) main auxiliary hoist
- Anti-two block device (overwind cutout)
- Boom angle indicator
- Tadano electronic load moment indicator system (AML-C)
- Outrigger extension length detector
- Electronic crane monitoring system
- Tadano twin swing system and 360° positive swing lock
- Self-centering finger control levers with pilot control
- Control pedals for boom hoist and boom telescoping
- 3-way adjustable cloth seat with armrests, high back and seat belt
- Tilt-telescoping steering wheel
- Tinted safety glass and sun visor
- Front windshield wiper and washer
- Roof window wiper and washer
- Power window (cab door)
- Rear-view mirrors (right and left side)
- Mirror for main and auxiliary hoists
- Cigarette lighter and ashtray
- Cab floor mat
- Pump disconnect in operator's cab
- Hydraulic oil cooler
- Hot water cab heater and air conditioner
- Telecommunications terminal (HELLO-NET Owner's Site)
- Positive control
- Quick-reeving type bi-fold jib
- Independently controlled outriggers
- Four outrigger extension positions
- Self-storing outrigger pads
- Outrigger hose protection
- Mitsubishi 6M60-TLA3B turbo charged after cooled engine (267HP) with exhaust brake
- Electronic controlled automatic transmission driven by torque converter
- 4 x 4 x 4 drive/steer
- Non-spin rear differential
- Automatic rear axle oscillation lockout system
- 29.5-25 22PR (OR) tires or 29.5-25 28PR (OR) tires
- Disc brakes
- Fenders
- Air dryer
- Water separator with filter (high filtration)

[VIEW DETAILS](#)